

# TECHNICAL INFORMATION

## ADHESIN 3182

### DESCRIPTION

**Type of adhesive** Synthetic Resin

**Field of application** **Packaging**  
Designed for use in paper converting applications and exhibits excellent specific adhesion, mechanical stability, as well as high flexibility with high strength when cured. This product is suitable for use on fast production lines and bonds well to a variety of coated papers and films and is ideal for "straight-line" glueing of packets.

### Product specification

**Viscosity** 1800 – 2600cps

**pH-value** 4.0 – 6.0

### Properties

**Film** This adhesive meets criteria for FDA CFR21 175.105 "INDIRECT FOOD ADDITIVES: ADHESIVES".

### Processing

**Application** Rollers

**Dilution** **ADHESIN 3182** is ready to use

**Cleaning** Water

**Disposal** See Safety Data Sheet

**Protective Measures**      See Safety Data Sheet

**Storage Conditions /  
Shelf Life**

In closed original packaging 12 months from date of production.  
Optimum storage temperature: 15 - 25 °C, protect from frost. Close containers thoroughly after use.

**DISCLAIMER**

Any information given is, to the best of our knowledge, the best currently available, with respect to our products and their use, but it is subject to revision as additional knowledge and experience is gained. Such information is offered as a guideline for experimentation only and is not to be construed as a representation that the material is suitable for any particular purpose or use. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use. This information is not a license to operate under nor is it intended to suggest infringement of any patent. We guarantee a uniform quality standard for this product. The only conditions and warranties accepted by Henkel in relation to this product or process are those implied by either Commonwealth or State statutes.